

serie big trailers 2023

platforms

Since 1960

ZACCARIA
QUALITY TRAILERS



platforms 2 axles

two axles

ZAM 120 A



two axles platform

Standard equipments:

Fixed floor with rear slope.
Hydraulic ramps mm. 500x2000.
Adjustable ramps (int. ramps 1050÷650).
Mechanical ramps support
Leaf springs suspensions.
Ramp operation lateral distributor.
Nr. 8 Lashing hooks.

On demand:

Front bar for round bales.
Front bar for bins.
Sheet metal top on the slope.
Spare wheels only for twin tires.
PVC Tool box.
Straight platform without slope.
Round bale support poles.
Patented system for tying round bales.
LED Lights.

MODEL	DIMENSIONS cm.	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Tons	TIRES	BRAKE	FLOOR HEIGHT cm.
ZAM 120 A	650x255	2	300x90 8 col.	2.2	12	215-75 R17.5 Twin new	Pneumatic	90
ZAM 120 B	650x255	2		2.2	12		Hydraulic	90

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

two axles close

TWO AXLES PLATFORM TANDEM SERIE 120

Standard equipments:

Fixed floor with
Hydraulic ramps mm. 500x2000.
Adjustable ramps (int. Ramps 1050÷650).
Mechanical ramps support.
Parabolic leaf springs suspensions
Hydraulic parking stand.
PVC Tool box.
Nr. 12 Lashing hooks.
Ramp operation lateral distributor.

Accessori On demand:

Front driven axle.
Front bar for round bales.
Front bar for bins.
Sheet metal surface on the rear slide.
Spare wheels only for twin tires.
Round bales support poles.
Patented system for tying round bales.
Hydraulic steering drawbar.
LED Lights.

platforms 2 axles



ZAM 120 ARI

MODEL	DIMENSIONS cm.	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Tons	TIRES	FLOOR HEIGHT	BRAKE
ZAM 120 ARP	650x255	2	300x90 8 col.	3.0	12	215/75 R17.5 twin used	88	Pneumatic
ZAM 120 ARI	650x255	2		3.0	12	on demand 215/75 R17.5 Twin new 400/60-15.5 new		Hydraulic

STANDARD COLOURS: monocolour

● RED ZACCARIA
● GREEN ZACCARIA
● GREEN JD ● Blue NH
● Black ● Grey JC246

OPTIONALS:

● metallic paint
● Personalized

platforms 2 axles

two axles

ZAM 140 B Super
Equiped with
Round bales tying system



platforms two axles

Standard equipments:

- Fixed floor with rear slope.
- Hydraulic ramps mm. 600x2200.
- Ajustable ramps (int. ramps 1250÷820).
- Hydraulic support system for ramps while loading.
- Leaf springs suspensions.
- PVC Tool box.
- Automatic brake regulator (with pneumatic brake).
- Nr. 12 Industrials lashing hooks.
- Rear panels and reflective side stripes.
- Lateral distributor for ramps.

On demand:

- Front bar for round bales.
- Front bar for bins.
- Sheet metal surface on the rear slide.
- Spare wheels only for twin tires.
- Patented system for tying round bales.
- Round bale support poles.
- Ramp distance adjustment with hydraulic control.
- Double ramps mm. 600x2000+1200.
- Wide ramps mm. 750x2200 (int. ramps 950÷520).

Aluminum hydraulic ramps mm. 750x2500.

Sides in UPN without edge.

- Hydraulic winch.
- LED Lights.

MODEL	DIMENSIONS cm.	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Tons	TIRES	FLOOR HEIGHT	BRAKE
ZAM 140 A SUPER	800x255	2	300x90 8 col.	3.8	14	215/75 R17,5 twin Pirelli new on demand	92	Pneumatic
ZAM 140 B SUPER	800x255	2		3.8	14	245/70 R17,5 twin Pirelli new	106	Hydraulic
						445/45R 19,5 single new		

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD Blue NH
- Black Grey JC246

OPTIONALS:

- metallic paint
- Personalized

PLATFORMS 2 AXLES

Standard equipments:

Parabolic leaf springs

Fixed floor with rear slope.
Hydraulic ramps mm. 750x2200.
Ajustable ramps (int. ramps 950÷520)
Hydraulic support system for ramps while loading.
PVC Tool box in PVC.
Automatic brake regulator.
Industrials lashing hooks.
Rear panels and reflective side stripes.
Sides marker lights.
Wheel cap nut.
Ramp operation lateral distributor.
Fixed drawbar.
Self-adjusting levers.
LED Lights.

On demand:

Front bar for round bales. Front bar for bins.
Spare wheels only for twin tires.
Double ramps mm. 750x2000+1200.
Aluminum hydraulic ramps mm. 750x2500.
Aluminum double ramps mm. 750x2650+950.
Grilled ramps mm 1200x2200.
Double grilled ramps mm 1200x2000+1200.
Hydraulic winch
Sides in UPN without edge.
Patented system for tying round bales.
Round bale support poles.
Ramp distance adjustment with hydraulic control.
Hidden rings and hooks for fixing.
New: Hydraulic suspensions



ZAM 180 P11A 80
Equipped with
Round bales tying system

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

New

Hydraulic suspensions
only with brake sizes 300x160

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	TARE Tons	GROSS W Max Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED approved** Europe	BRAKE
ZAM 180P11A 65	650x255	2	300x160 industrial axles with 10 studs	3.1	18	245/70 R17,5 twin	98 cm	435/50 R19,5 Sin	100 cm		Pneumatic
ZAM 180P11A 80	800x255	2		3.9	18			445/45 R19,5 Sin	100 cm		
ZAM 180P11A 93	930x255	2		4.5	18						

platforms 2 axles



**MODEL ZAM 180 P11B 93
with Double ramps
& Round bales tying system**



STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

New

Hydraulic suspensions
only with brake sizes 300x160

New

A.B.S. anti-lock brake system

PLATFORMS 2 AXLES

Standard equipments:

Oversized structure for special loads.

- Fixed floor with rear slope.
- Hydraulic ramps mm. 750x2200.
- Adjustable ramps (int. ramps 950÷520)
- Hydraulic support system for ramps while loading.
- PVC Tool box in PVC.
- Automatic brake regulator.
- Industrials lashing hooks.
- Rear panels and reflective side stripes.
- Aluminum side underride bars.
- Sides marker lights.
- Oversized industrial rims. Wheel cap nut.
- Ramp operation lateral distributor.
- Fixed drawbar.
- Self-adjusting levers.
- LED Lights.

On demand:

- Front bar for round bales.
- Front bar for bins.
- Spare wheels only for twin tires.
- Round bales tying system with central pole.
- Ramp distance adjustment with hydraulic control.
- Double ramps mm. 750x2000+1200.
- Aluminum hydraulic ramps mm. 750x2500.**
- Aluminum double ramps mm. 750x2650+950.**
- Grilled ramps mm 1200x2200.
- Double grilled ramps mm 1200x2000+1200.
- Hydraulic winch.

Sides in UPN without edge.

- Round bale support poles.
- Hidden rings and hooks for fixing.

Height-adjustable self-supporting frame.

New: Hydraulic suspensions.

New: A.B.S. anti-lock brake system.

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	BRAKE SIZE OPTION	TARE Tons	GROSS W. Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED approved** Europe	BRAKE
ZAM 180 P11B 80	800x255	2	300x160 industrial axles with 10 studs	310x190 industrial axles with 10 studs	4.3	18	245/70 R17,5 twin	98 cm	435/50 R19,5	100 cm 100 cm		Pneumatic
ZAM 180 P11B 93	930x255	2			4.5	18			445/45 R19,5			



ZAM 140 AR - ZAM 140 AR SUPER
also available in **TILTING VERSION**
with rear loading board

platforms

2 axles

TWO AXLES PLATFORM TANDEM

Standard equipments:

Fixed floor with rear slope.
Hydraulic ramps mm. 600x2200.
Adjustable ramps (int. ramps 1250÷820).
Hydraulic support system for ramps while loading.
Steering rear axle.
Leaf springs suspensions.
Hydraulic parking stand. PVC Tool box.
Automatic brake regulator (with pneumatic brake).
Nr. 12 Industrials lashing hooks.
Rear panels and reflective side stripes.
Ramp operation lateral distributor.

On demand:

Front driven axle.
Front bar for round bales. Front bar for bins.
Steering adjuster. Sheet metal surface on the rear slide.
Spare wheels only for twin tires.
Double ramps mm. 750x2000+1200.
Wide ramps mm. 750x2200 (int. 950÷520).

Aluminum hydraulic ramps mm. 750x2500.

Hydraulic winch

Sides in UPN without edge.

Patented system for tying round bales.
Round bale support poles.
Ramp distance adjustment with hydraulic control.
Hydraulic steering drawbar.
Height-adjustable self-supporting frame.
LED Lights.

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

two axles close

**ZAM 140 ARI
Super**



STEERING DRAWBAR

New optional:

Hydraulic Steering Drawbar
hydraulic operated by the distributor
directly from the tractor APPROVED

MODEL	DIMENSIONS cm.	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Tons	TIRES	FLOOR HEIGHT	BRAKE
ZAM 140 ARP	650x255	2	300x90 8 col.	3.0	14	215/75 R17,5 Twin Pirelli new on demand 245/70 R17,5 Twin Pirelli new	88	Pneumatic
ZAM 140 ARI	650x255	2		3.0	14		91	Hydraulic
ZAM 140 ARP SUPER	800x255	2		3.6	14	445/45R 19,5 single new	100	Pneumatic
ZAM 140 ARI SUPER	800x255	2		3.6	14			Hydraulic

platforms 2 axles

two axles close



MODEL ZAM 180 P02A 80
equipped with
Round bales tying system
Patented system



STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

New
Hydraulic suspensions
only with brake sizes 300x160

TWO AXLES PLATFORM TANDEM

Standard equipments:

2° Steering axle.

Parabolic leaf springs

Fixed floor with rear slope.

Hydraulic ramps mm. 750x2200.

Ajustable ramps (int. ramps 950÷520)

Hydraulic support system for ramps while loading.

PVC Tool box. Hydraulic parking stand.

Automatic brake regulator.

Nr. 12 Industrials lashing hooks.

Rear panels and reflective side stripes.

Sides marker lights.

Wheel cap nut.

Ramp operation lateral distributor.

Fixed drawbar.

Self-adjusting levers.

LED Lights.

On demand:

Front bar for round bales.

Front bar for bins.

Spare wheels only for twin tires.

Patented system for tying round bales.

Round bale support poles.

Ramp distance adjustment with hydraulic control.

Double ramps mm. 750x2000+1200.

Aluminum hydraulic ramps mm. 750x2500.

Aluminum double ramps mm. 750x2650+950.

Double grilled ramps mm 1200x2000+1200.

Hydraulic winch

Sides in UPN without edge.

Hidden rings and hooks for fixing.

Hydraulic steering drawbar.

Height-adjustable self-supporting frame.

New: Hydraulic suspensions.

K80 Towing eye bolted.

Bolted Towing eye 40mm.

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Max Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED approved** Europe	BRAKE
ZAM 180 P02A 65	650x255	2	300x160 10 studs	4.0	18	245/70 R17,5 twin Pirelli new	92 cm	435/50 R19,5 single new	100 cm		Pneumatic
ZAM 180 P02A 80	800x255	2		4.5	+vertical load max 4 tons			445/45 R19,5 single new			

platforms 2 axles

TWO AXLES PLATFORM TANDEM

Standard equipments:

2° Steering axle.

Parabolic leaf springs

Fixed floor with rear slope.

Hydraulic ramps mm. 750x2200.

Ajustable ramps (int. ramps 950+520)

Hydraulic support system for ramps while loading.

PVC Tool box. Hydraulic parking stand.

Automatic brake regulator.

Industrials lashing hooks.

Rear panels and reflective side stripes.

Aluminum side underride bars.

Sides marker lights.

Oversized industrial rims. Wheel cap nut.

Ramp operation lateral distributor.

Fixed drawbar.

Self-adjusting levers.

LED Lights.

On demand:

Front bar for round bales.

Front bar for bins.

Spare wheels only for twin tires.

Patented system for tying round bales.

Round bale support poles.

Ramp distance adjustment with hydraulic control.

Double ramps mm. 750x2000+1200.

Aluminum hydraulic ramps mm. 750x2500.

Aluminum double ramps mm. 750x2650+950.

Double grilled ramps mm 1200x2000+1200.

Hydraulic winch

Sides in UPN without edge.

Platform with wooden surface.

Hidden rings and hooks for fixing.

Hydraulic steering drawbar.

Height-adjustable self-supporting frame.

New: Hydraulic suspensions.

New: A.B.S. anti-lock brake system.

K80 Towing eye bolted.

Bolted Towing eye 40mm.



two axles close

MODEL ZAM 180 P02B



STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

New
A.B.S. anti-lock brake system

New
Hydraulic suspensions
only with brake sizes 300x160

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	BRAKE SIZE OPTIONAL	TARE Tons	GROSS W. Max Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED approved** Europe	BRAKE
ZAM 180 P02B 65	650x255	2	300x160 industrial axles with 10 studs	310x190 industrial axles with 10 studs	4.3	18 +vertical load max 4 tons	245/70 R17,5 twin Pirelli new	92 cm	435/50 R19,5 single new	100 cm	60 Km/h	Pneumatic
ZAM 180 P02B 80	800x255	2			4.8				445/45 R19,5 single new			

platforms 3 axles



ZAM 270 P03A 98



STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246 ● Personalized

OPTIONALS:

- metallic paint
- Personalized

New
Hydraulic suspensions
only with brake sizes 300x160

PLATFORMS with 3 AXLES close

Standard equipments:
1° e 3° steering axles.
Parabolic leaf springs

- Fixed floor with rear slope.
- Hydraulic ramps mm. 750x2200.
- Ajustable ramps (int. ramps 950÷520).
- Hydraulic support system for ramps while loading.
- PVC Tool box. Hydraulic parking stand.
- Steering adjuster.
- Automatic brake regulator.
- Industrials lashing hooks.
- Rear panels and reflective side stripes.
- Sides marker lights.
- Oversized industrial rims. Wheel cap nut.
- Ramp operation lateral distributor.
- Fixed drawbar.
- Self-adjusting levers.
- Hidden rings and hooks for fixing.
- LED Lights.

On demand:

- Front bar for round bales.
- Front bar for bins.
- Spare wheels only for twin tires.
- Patented Round bales tying system
- Ramp distance adjustment with hydraulic control.
- Double ramps mm. 750x2000+1200.
- Aluminum hydraulic ramps mm. 750x2500.**
- Aluminum double ramps mm. 750x2650+950.**
- Grilled ramps mm 1200x2200+1200.
- Double grilled ramps mm 1200x2000+1200.
- Hydraulic winch
- Sides in UPN without edge.**
- Hydraulic steering drawbar.**
- Height-adjustable self-supporting frame.**
- New: Hydraulic suspensions.**
- K80 Towing eye bolted.
- Bolted Towing eye 40mm.

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED	BRAKE
ZAM 270 P03A 70	700x255	3	300x160 industrial axles with 10 studs	4.7	27 +vertical load max 4 tons	245/70 R17,5 Twin new Pirelli	94 cm	435/50 R19,5 single new 445/45 R19,5 single new	102 cm		Pneumatic
ZAM 270 P03A 85	850x255	3		5.3							
ZAM 270 P03A 98	980x255	3		5.7							

PLATFORMS 3 AXLES close

Standard equipments:

1° and 3° steering axles.

Parabolic leaf springs

Oversized structure for special loads.

Fixed floor with rear slope.

Hydraulic ramps mm. 750x2200.

Ajustable ramps (int. ramps 950+520).

Hydraulic support system for ramps while loading.

PVC Tool box. Piedino idraulico.

Steering adjuster.

Automatic brake regulator.

Industrials lashing hooks.

Rear panels and reflective side stripes.

Aluminum side underride bars.

Sides marker lights.

Oversized industrial rims. Wheel cap nut.

Ramp operation lateral distributor.

Fixed drawbar. Self-adjusting levers.

LED Lights.

On demand:

Front bar for round bales.

Front bar for bins.

Spare wheels only for twin tires.

Patented Round bales tying system.

Ramp distance adjustment with hydraulic control.

Double ramps mm. 750x2000+1200.

Aluminum hydraulic ramps mm. 750x2500.

Aluminum double ramps mm. 750x2650+950.

Grilled ramps mm 1200x2200.

Double grilled ramps mm 1200x2000+1200.

Hydraulic winch

Sides in UPN without edge.

Platform with wooden surface.

Hidden rings and hooks for fixing.

Hydraulic steering drawbar.

Height-adjustable self-supporting frame.

New: Hydraulic suspensions.

New: A.B.S. anti-lock brake system.

K80 Towing eye bolted.

Bolted Towing eye 40mm.



3 axles platforms

three axles close

ZAM 270 P03B 98
equipped with wooden susface



New

Hydraulic suspensions
only with brake sizes 300x160

New

A.B.S. anti-lock brake system

STANDARD COLOURS:
monocolour

● RED ZACCARIA

● GREEN ZACCARIA

● GREEN JD ● Blue NH

● Black

● Grey JC246

OPTIONALS:

● metallic paint

● Personalized

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	BRAKE SIZE OPTIONAL	TARE Tons	GROSS W. Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED	BRAKE
ZAM 270 P03B 70	700x255	3	300x160 industrial axles with 10 studs	310x190 industrial axles with 10 studs	5.0	27 +vertical load max 4 tons	245/70 R17,5 Twin new Pirelli	91 cm	435/50 R19,5 single new 445/45 R19,5 single new	102 cm		Pneumatic
ZAM 270 P03B 85	850x255	3			5.6							
ZAM 270 P03B 98	980x255	3			6.0							

platforms 3 axles

PLATFORMS 3 AXLES WITH FRONTAL BEARING DISC

Standard equipments:

Assale posteriore autosterzante.
Fixed floor with rear slope.
Hydraulic ramps mm. 600x2200.
Adjustable ramps (int. ramps 1250÷820).
Hydraulic support system for ramps while loading.
Parabolic leaf springs suspensions with rod
PVC Tool box.
Automatic brake regulator.
(with pneumatic brake).
Nr. 12 Industrials lashing hooks.
Rear panels and reflective side stripes.
Ramp operation lateral distributor.
Steering adjuster.

On demand:

Front bar for round bales.
Front bar for bins.
Spare wheels only for twin tires.
Patented Round bales tying system.
Round bale support poles.
Ramp distance adjustment with hydraulic control.
Double ramps mm. 750x2000+1200.
Wide ramps mm. 750x2200 (int. ramps 950÷520).
Aluminum hydraulic ramps mm. 750x2500.
Aluminum double ramps mm. 750x2650+950.
Grilled ramps mm 1200x2200.
Double grilled ramps mm 1200x2000+1200.
Sides in UPN without edge.
Hydraulic winch
LED Lights.

Equipped with round bale support poles

ZAM 200 P MAXI

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

TIRES APPROVED

215/75R17.5
Twin new
L. 215 - H. 78

245/70R17.5
Twin new
L. 245 - H. 80

445/45R19.5
new
L. 44.5 - H. 90



MODEL	DIMENSIONS cm.	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Tons	TIRES	FLOOR HEIGHT	BRAKE
ZAM 200 P	850x255	3	300x135 industrial 10 studs	5.0	20	215/75 R17.5 Twin Pirelli new on demand 245/70 R17.5 Twin Pirelli new 445/45R 19.5 single new	92	Pneumatic
ZAM 200 I	850x255	3		5.0	20		94	Hydraulic
ZAM 200 P MAXI	1020x255	3		5.7	20		106	Pneumatic
ZAM 200 I MAXI	1020x255	3		5.7	20			Hydraulic

PLATFORMS 3 AXLES

Standard equipments:

3° Steering axle.

Parabolic leaf springs

Fixed floor with rear slope.

Hydraulic ramps mm. 750x2200.

Ajustable ramps (int. ramps 950÷520).

Hydraulic support system for ramps while loading.

PVC Tool box. Steering adjuster.

Automatic brake regulator.

Industrials lashing hooks.

Rear panels and reflective side stripes.

Sides marker lights.

Oversized industrial rims. Wheel cap nut.

Ramp operation lateral distributor.

Fixed drawbar.

Self-adjusting levers.

LED Lights.

MODEL ZAM 240 EXTRALONG with:

Hydraulically operated extendable drawbar.

On demand:

Front bar for round bales.

Front bar for bins.

Spare wheels only for twin tires.

Patented Round bales tying system.

Ramp distance adjustment with hydraulic control.

Double ramps mm. 750x2000+1200.

Aluminum hydraulic ramps mm. 750x2500.

Aluminum double ramps mm. 750x2650+950.

Grilled ramps mm 1200x2200.

Double grilled ramps mm 1200x2000+1200.

Hydraulic winch

Sides in UPN without edge.

Hidden rings and hooks for fixing.

Height-adjustable self-supporting frame.

New: Hydraulic suspensions.



ZAM 240 P12A MAXI
equipped with Patented
round bales tying
system

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246

OPTIONALS:

- metallic paint
- Personalized

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	TARE Tons	GROSS W. Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED	BRAKE
ZAM 240 P12A	850x255	3	front 300x160 rear 300x135 industrial axles with 10 studs	5.9	24	215/75 R17,5 Twin Pirelli new	94 cm	245/70 R17,5 Twin Pirelli New	98 cm		Pneumatic
ZAM 240 P12A MAXI	1020x255	3		6.4	24						
ZAM 240 P12A EXTRALONG	1075x255	3		6.7	24						

platforms 3 axles

OMOLOGATI MOTHER REGULATION
24
TONS



ZAM 240 P12B MAXI
Equipped with Double ramps and
Patented Round bales tying system

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH
- Black ● Grey JC246
- Personalized

OPTIONALS:

- metallic paint
- Personalized

New
Hydraulic suspensions
only with brake sizes 300x160

New
A.B.S. anti-lock brake
system

PLATFORMS 3 AXLES Standard equipments:

- 3° Steering axle.
- Parabolic leaf springs.
- Oversized structure for special loads.
- Fixed floor with rear slope.
- Hydraulic ramps mm. 750x2200.
- Ajustable ramps (int. ramps 950÷520).
- Hydraulic support for ramps while loading.
- PVC Tool box. Steering adjuster.
- Automatic brake regulator.
- Industrials lashing hooks.
- Rear panels and reflective side stripes.
- Aluminum side underride bars.
- Sides marker lights.
- Oversized industrial rims. Wheel cap nut.
- Ramp operation lateral distributor.
- Fixed drawbar.
- Self-adjusting levers.
- LED Lights.

MODEL ZAM 240 EXTRALONG: Hydraulically operated extendable drawbar

On demand:

- Front bar for round bales.
- Front bar for bins.
- Spare wheels only for twin tires.
- Patented system for tying round bales.
- Ramp distance adjustment with hydraulic control.
- Double ramps mm. 750x2000+1200.
- Aluminum hydraulic ramps mm. 750x2500.
- Aluminum double ramps mm. 750x2650+950.
- Grilled ramps mm 1200x2200.
- Double grilled ramps mm 1200x2000+1200.
- Hydraulic winch.
- Sides in UPN without edge.
- Platform with wooden surface.
- Hidden rings and hooks for fixing.
- Height-adjustable self-supporting frame.
- New: Hydraulic suspensions.
- New: A.B.S. anti-lock brake system.

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	BRAKE SIZE OPTION	TARE Tons	GROSS W. Max Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED approved** Europe	BRAKE
ZAM 240 P12B	850x255	3	front 300x160 rear 300x160 industrial axles with 10 studs	310x190 industrial axles with 10 studs	5.9	24	215/75 R17,5 Twin Pirelli (Tons 238)	94 cm	245/70 R17,5 Twin Pirelli (Tons 240)	98 cm		Pneumatic
ZAM 240 P12B MAXI	1020x255	3			6.4	24						
ZAM 240 P12B EXTRALONG	1075x255	3			6.7	24						

** Dove permesso secondo il Codice Stradale del Paese Comunitario.

PLATFORMS 4 AXLES

Standard equipments:

2° e 4° Steering axle.

Parabolic leaf springs

Fixed floor with rear slope.

Hydraulic ramps mm. 750x2200.

Ajustable ramps (int. ramps 950÷520).

Hydraulic support system for ramps while loading.

PVC Tool box. Steering adjuster.

Automatic brake regulator.

Nr. 12 Industrials lashing hooks.

Rear panels and reflective side stripes.

Aluminum side underride bars.

Sides marker lights.

Oversized industrial rims. Wheel cap nut.

Ramp operation lateral distributor.

Fixed drawbar.

Self-adjusting levers.

LED Lights.

On demand:

Front bar for round bales. Front bar for bins.

Spare wheels only for twin tires.

Patented Round bales tying system.

Round bale support poles.

Ramp distance adjustment with hydraulic control.

Double ramps mm. 750x2000+1200.

Aluminum hydraulic ramps mm. 750x2500.

Aluminum double ramps mm. 750x2650+950.

Grilled ramps mm 1200x2200.

Double grilled ramps mm 1200x2000+1200.

Hydraulic winch.

Sheet metal surface on the rear slide.

Sides in UPN without edge.

Platform with wooden surface.

Hidden rings and hooks for fixing.

Height-adjustable self-supporting frame.

New: Hydraulic suspensions.

New: A.B.S. anti-lock brake system.



MODEL ZAM 320 P EXTRALONG:

Hydraulically operated extendable drawbar



ZAM 320 P13B MAXI

New

Hydraulic suspensions
only with brake sizes 300x160

New

A.B.S. anti-lock brake system

STANDARD COLOURS:
monocolour

RED ZACCARIA

GREEN ZACCARIA


GREEN JD Blue NH

Black Grey JC246

OPTIONALS:

metallic paint

Personalized

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	BRAKE SIZE OPTION	TARE Tons	GROSS W. Max Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED approved** Europe	BRAKE
ZAM 280 P13B	850x255	4	300x160 industrial axles with 10 studs	310x190 industrial axles with 10 studs	7.5	28	215/75 R17,5 twin	94 cm	235/70 R17,5 Twin Pirelli new 245/70 R17,5 Twin Pirelli new (Tons 320) 445/45 - 19-5	98 cm		Pneumatic
ZAM 320 P13B MAXI	1020x255	4			7.7	32	215/75 R17,5 twin (Tons 318)	94 cm		98 cm		
ZAM 320 P13B EXTRALONG	1075x255	4			8.0	32				98 cm		

platforms

4 AXLES

double front axle

ZAM 320 P22B EXTRALONG

Hydraulically operated extendable drawbar

New
Hydraulic suspensions
only with brake sizes 300x160

New
A.B.S. anti-lock brake system

PLATFORMS 4 AXLES

Standard equipments:

4° Steering axle.

Parabolic leaf springs
Fixed floor with rear slope.
Hydraulic ramps mm. 750x2200.
Adjustable ramps (int. ramps 950÷520).
Hydraulic support system for ramps while loading.
PVC Tool box. Steering adjuster.
Automatic brake regulator.
Nr. 12 Industrials lashing hooks.
Rear panels and reflective side stripes.
Aluminum side underride bars.
Sides marker lights.
Oversized industrial rims. Wheel cap nut.
Ramp operation lateral distributor.
Fixed drawbar.
LED Lights.
Self-adjusting levers.

On demand:

Front bar for round bales. Front bar for bins.
Spare wheels only for twin tires.
Patented Round bales tying system.
Round bale support poles.
Ramp distance adjustment with hydraulic control.
Double ramps mm. 750x2000+1200.
Aluminum hydraulic ramps mm. 750x2500.
Aluminum double ramps mm. 750x2650+950.
Grilled ramps mm 1200x2200.
Double grilled ramps mm 1200x2000+1200.

Hydraulic winch

Sides in UPN without edge.

Platform with wooden surface.

Hidden rings and hooks for fixing.

Height-adjustable self-supporting frame.


New: Hydraulic suspensions.

New: A.B.S. anti-lock brake system.

STANDARD COLOURS: monocolour

- RED ZACCARIA
- GREEN ZACCARIA
- GREEN JD ● Blue NH ● metallic paint
- Black ● Grey JC246 ● Personalized

OPTIONALS:

MODEL	DIMENSIONS cm	AXLES	BRAKE SIZE	BRAKE SIZE OPTIONAL	TARE Tons	GROSS W. Tons	TIRES Standard	FLOOR HEIGHT	TIRES on demand	FLOOR HEIGHT	SPEED approved** Europe	BRAKE
ZAM 300 P22B	850x255	4	300x160 industrial axles with 10 studs	310x190 industrial axles with 10 studs	7.5	30	front 215/75 R17,5 Twin Pirelli new	94 cm	front 245/70 R17,5 Twin Pirelli new	98 cm		Pneumatic
ZAM 320 P22B MAXI	1020x255	4			7.7	32	rear 245/70 R17,5 Twin Pirelli new		rear 245/70 R17,5 Twin Pirelli new			
ZAM 320 P22B EXTRALONG	1075x255	4			8.0	32	245/70 R17,5 Twin Pirelli new		245/70 R17,5 Twin Pirelli new			

specials

Platforms for Industrial use

Exceptional vehicle
FLOOR HEIGHT 13 mt.
Load 40 Tons.



Our Technical office
Project with 3D software
Equipment «Big Trailers»
Operating machines & Special
Trailers with European
or Italian approval



ZAM 140 P Super
Equipped for animal transport



PLATFORMS with frame
and various models of ramps



ZAM 270 P03B 98 with Hydraulic
traction



OPTIONAL:
Hydraulic Traction

platforms



**Double hydraulic ramps
size 200+120x75**



**Grilled ramps
from 120x220 cm**



**Grilled double ramps
from 200x120x120 cm**



Sheet metal surface on the rear slide.



equipped with poles for trunks

platforms



Hydraulic winch



Sides in UPN without edge



K80 Towing Eye



Led lights



Wooden surface for tracked metal machines



Bolted Towing eye

accessories

platforms



zaccariarimorchi.com

ZACCARIA

QUALITY TRAILERS



ZACCARIA SRL

Via Enrico Fermi, 350

I - 41055 Montese (Modena) - Italy


Tel. +39 (0)59 981750

Fax: +39 (0)59 982353


www.zaccariarimorchi.com

info@zaccariarimorchi.com

 www.facebook.com/zaccariarimorchi

 www.linkedin.com/company/zaccaria-srl

 www.youtube.com/zaccariatrailer

 www.instagram.com/zaccaria_rimorchi

Branches & Warehouse

I - 41015 Nonantola (Modena)

Via Zuccola, 12 - Italy



Scan the QR CODE

To view

Our VIDEO

[zaccaria trailers youtube](https://www.youtube.com/zaccariatrailer)

